

Applications

Ductaire® Titan Ducted Fume Cabinets offer the best possible features and quality in a Ducted Fume Cupboard.

- » Laboratory, Pharmaceutical and Industrial Analytical Research
- » Industrial, Medical and Educational Establishments requiring extraction systems for operator protection.

Standard features

- » Outer Carcass fabricated from Zintec Mild Steel Powder Coated in Textured Matt White (RAL9016).
- » 6mm Toughened Glass Sash, includes stops set at 500mm and 25mm.
- » Alarm System - LCD Air Speed read-out, Fan stop/start and programmable relay outputs and inputs.
- » Interior 55W, Low Energy Lighting.
- » Extraction Fans fabricated from Polypropylene available for single or three phase supply.
- » Removable back baffle for easy cleaning and maintenance.
- » Fully BS EN 14175 & COSHH compliant.

Optional Features

A wide range of Highly Chemical Resistant work surfaces available, including:

- » Solid Grade Laminate (Trespa),
- » Solid Epoxy Resin,
- » Fully Welded Polypropylene,
- » 316 Grade Stainless Steel.

Available cabinet options

- » Bench Mounted
- » Step In
- » Walk In
- » Double Chamber
- » Variable Air Volume
- » Control System (VAV)
- » Automatic Safety Sash



	DT1000	DT1200	DT1500	DT1800	DT2000
Ext. Dimensions	1000x2400x900mm	1200x2400x900mm	1500x2400x900mm	1800x2400x900mm	2000x2400x900mm
Int. Dimensions	700x1100x720mm	900x1100x720mm	1200x1100x720mm	1500x1100x720mm	1700x1100x720mm
Air Volume	0.175m ³ /sec	0.225m ³ /sec	0.30m ³ /sec	0.375m ³ /sec	0.425m ³ /sec
Weight	200kg	225kg	250kg	275kg	300kg
Power	230V/20A				